

MSP 245 STAR | REPORT PRINTER

The financial star











Printing speed of 450 cps - Faster printing



15,000 power on hours -Higher reliability



Excellent copy capability
- Prints 1+4 copies



Printer built-in barcode fonts - Prints barcodes



200 Million character print head life -Trouble-free printing



Selicon self-lubrication mechanism -Maintenance free. No more interruptions



The MSP 245 Star Advantage

The new 'Turbodot' print head from TVS-E is designed and precision engineered to obtain the best results.

Sealed coils enhance the thermo-cooling capacity of the print head.

In comparison to the conventional tungsten pins, the HSS (High Speed Steel) Pins used in 'Turbodot' print head ensure precise dot placement.

The exterior of the print head is designed with increased number of Heat Sink Fins for better heat dissipation.

A special exterior coating on Heat Sink enhances heat dissipation.

The specially designed Plastic Front Profile guarantees smooth ribbon movement, thus slowing the wear and tear of the ribbon fabric and improving ribbon life.

Specifications

Print Method : Serial impact dot matrix
Print Direction : Bi-directional logic seeking

Print Head Type : 9 wire
Print Width : 136 column

Print Head Life : 200 million characters#

Positioning Speed : 450 cps

Print Speed

 Character Pitch (cpi)
 : 10
 12
 15

 High Speed Draft (cps)
 : 380
 450

 Draft (cps)
 : 300
 360
 450

 Near Letter Quality
 : 75
 90

(cps)

Resident Printer Fonts

High Speed Draft : Standard 10 and 12 cpi

Draft : Standard 10, 12, 15, 17 and 20 cpi

Near Letter Quality : Roman, Sans Serif, Script

Resident Barcode : Code 3 of 9

Paper Handling

Paper Path - : Top, rear and bottom

Standard
Continuous Tractor : Convertible push and pull

Feed - Standard

Paper Size

Continuous Form : 4" - 16"

Width

Cut Sheet Width : 7.2" - 16.1'
Paper Thickness : 0.3 mm

(max) - Tractor Feed

: 7.2" - 16.1"

CUSTOMER SEGMENTS



Trading & Distribution Companies



Manufacturing Companies



Logistic Providers



Financial Institutions

TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor, Industrial Estate, Guindy, Chennai - 600 032.

Call: 1800 200 5123 / 3030 9797 / 3030 7171 (prefix city STD code)

Visit: www.tvs-e.in

Paper Thickness : 0.3 mm

(max) - Friction Feed

Copy Capability* : 1+4 with carbon

Consumables - Ribbon

Type : Patented TVS-E ribbon cassette with user

replaceable Ink bank

Colour : Jet black

Ribbon Life : 40 million characters with 3 additional

Ink banks

Cassette Refill Mode : Through Ink bank
Ink bank Life : 10 million characters**

Input Buffer : 100 KB (Kilo Bytes)

Reliability

MTBF : 15000 POH##

(Power on Hours)

Acoustics : 55 dB (A) in ISO 7779 Sonic Pattern

(Noise Level)

Emulation : ESC / P, IBM Proprinter

Interface

Standard : Centronics IEEE - P1284A Parallel, USB

Optional : RS-232C serial###

Software Specifications

Drivers : Windows 95, 98, NT, Me, 2000, XP, Vista, Win

7, Win 8 & Linux

Electronic Guide : HTML based

Electrical Specifications

Operating Voltage : 150V - 270 V AC Mains Frequency : 47 - 63 Hz Power (Standby) : ~12 W

Environmental - Operating Conditions

Temperature : 0° to +45°C Relative Humidity : 10% to 80%

Physical Dimensions

Size (W x D x H) mm : $608 \times 379 \times 147$

Weight : 7 kg Warranty : 1 year

Best suited for printing

Invoices I Ledgers I Accounts & Statements I Reports I Journals I Legal Documents

ORDERING INFORMATION

3014060011 MSP 245 STAR

OPTIONAL CONSUMABLES

2028010011 TVS-E RIBBON CASSETE 136 COL

2017100041 TVS-E INK BANK 2023020061 TVS-E PRINT HEAD

MSP 245 STAR

DEALER STAMP

¹ kg = 2.2 lbs; 1 inch = 2.54 cms

^{*}Max. possible copy capability

^{**@} Draft 10 cpi

^{#@ 33%} print density and 25% duty cycle

 $[\]ensuremath{^{\#}}$ Excluding print head @ 33% print density and 25% duty cycle

^{***.} in lieu of USB